

C-1800 AccelAir 2

The C-1800 Fibre Blowing Machine (Accelair 2) has been developed to provide a simple to use and reliable fibre blowing solution. The Accelair 2 is designed to fit a fibre range from 1 to 3mm diameter, thereby providing the complete range of blown fibre installation solutions from one machine.

The Accelair 2 is a compact integrated fibre blowing machine benefiting from full automation and fibre management; sophisticated fibre protection is implemented to ensure the fibre mechanical and optical integrity is maintained. The machine only requires a single 24V D.C. electrical supply and compressed air to operate.



SPECIFICATION

- Fibre Compatibility:** Up to 2mm with buckle, up to 3mm without buckle
- Blowing Speed:** Manual control to 50 metres per minute
- Compatible Tubes:** Any size from 3mm to 10mm
- Automation:** In buckle mode machine is self-regulating
- Air Supply:** 15 Bar max working pressure complete with suitable air conditioning (drying)
- Electrical Supply:** Universal mains power supply (supplied as standard): 85-265V AC 47-63Hz or 120-370V DC input, 24V DC 2.2A output. Battery pack and vehicle adaptor available upon request.
- Control:** Remote user interface with backlit screen provides all necessary information; including current distance, speed, torque setting and fibre status.
- Machine size:** H: 166mm D: 184mm x 120mm. Weight: 3kg.
- Case size:** H: 220mm D: 480mm x 430mm. Weight (all in): 12kg



ORDERING DETAILS

Product No	Description
C-1800	Accelair 2 Fibre Blowing Machine c/w Power Cable, Universal Mains Supply and carry case

Machine custom set for your fibre.

For Further Information

Telephone No: +44(0) 1572 723665 • Fax No: +44 (0) 1572 756009
 E-mail: sales@cbsproducts.com • Website: www.cbsproducts.com